



Vicortex



Visone

Technical Specifications

	Roll Length	~ 40 m	
	Roll Width	142 cm (+/-2%)	
	Surface Composition	100% Polyester	
	Base Composition	100% Polyester	
	Weight m ² DIN EN 12127	370 g/m² (+/-5%)	
	Thickness +/- 2%	2,1 mm	
	Abrasion Test EN ISO 12947-1,2	>45.000	
	Pilling EN ISO 12945-2 (2.000T)	4-5	
	Tensile Strength EN ISO 13934-1	Warp: 4-5	Weft: 4-5
	Tear Growth Resistance EN ISO 13937-3	Warp: 95N	Weft: 50N
	Color Fastness to Light EN ISO 105-B02	4-4.5	
	Color Fastness to Rubbing EN ISO 105-X12	Dry: 4	Wet: 4



The analytical results are referred only to the sample tested. Discolouration and colour deviations tolerated by permissible industrial standards which do not constitute reasons for claim. We reserve the right to modify, at any moment and without notice any product specifications.



Vicortex



Clean and Care recommendations



Machine Wash



Do Not Use Bleach



Iron maximum 110°



Dry Cleaning



Tumble Dry

Wash to machine, maximum 40°, do not use abrasive products or neutral detergents. Iron maximum at 110° and always in the back side. It admits dry clean.



We develop our articles by applying new technologies in the production process, so that this fabric is conscious of the environment and people's health.



By taking proper care of the fabric, you will ensure that it stays as good as new for a longer period of time. That's why we ask you to take the following tips into account:

- Do not expose your new sofa to direct sunlight.
- Do not place your new sofa near heaters, radiators, fireplaces, etc.
- Avoid contact with your new sofa with rough fabrics, which can cause transfers.
- Try to suck up and remove the usual dust and dirt from your home with a vacuum cleaner at low power.