



# Vicortex



# Otaria

## Technical Specifications

	Roll Length	~ <b>40 m</b>	
	Roll Width	<b>140 cm</b> (+/-2%)	
	Surface <b>Composition</b>	<b>100% Polyester</b>	
	Base <b>Composition</b>	<b>100% Polyester</b>	
	Weight m <sup>2</sup>   DIN EN 12127	<b>420 g/m<sup>2</sup></b> (+/-5%)	
	Thickness   +/- 2%	<b>1,2 mm</b>	
	Abrasion Test   EN ISO 12947-1,2	<b>&gt;45.000</b>	
	Pilling   EN ISO 12945-2 (2.000T)	<b>4-5</b>	
	Tensile Strength   EN ISO 13934-1	Warp: <b>4-5</b>	Weft: <b>4-5</b>
	Tear Growth Resistance   EN ISO 13937-3	Warp: <b>78N</b>	Weft: <b>40N</b>
	Color Fastness to Light   EN ISO 105-B02	<b>4</b>	
	Color Fastness to Rubbing   EN ISO 105-X12	Dry: <b>4</b>	Wet: <b>4</b>



The analytical results are referred only to the sample tested. Discolouration and colour deviations tolerated by permissible industrial standards which do not constitute reasons for claim. We reserve the right to modify, at any moment and without notice any product specifications.



#### Clean and Care recommendations



Machine Wash



Do Not Use Bleach



Iron maximum 110°



Dry Cleaning



Do Not Tumble Dry

---

Wash to machine, maximum 30°, do not use abrasive products or neutral detergents. Iron maximum at 110° and always in the back side. It admits dry clean, only by professionals.

---



We develop our articles by applying new technologies in the production process, so that this fabric is conscious of the environment and people's health.

---



By taking proper care of the fabric, you will ensure that it stays as good as new for a longer period of time. That's why we ask you to take the following tips into account:

- Do not expose your new sofa to direct sunlight.
- Do not place your new sofa near heaters, radiators, fireplaces, etc.
- Avoid contact with your new sofa with rough fabrics, which can cause transfers.
- Try to suck up and remove the usual dust and dirt from your home with a vacuum cleaner at low power.